

Double row angle contact bearing

Bearing Designation	Boundary Dimensions(mm)			Mass (kg)	Bearing Designation	Boundary Dimensions(mm)			Mass (kg)
	d	D	B	Approx		d	D	B	Approx
3200	10	30	14.3	0.052	5310	50	110	44.4	1.93
3201	12	32	15.9	0.063	3211	55	100	33.3	1.05
3202	15	35	15.9	0.072	5211	55	100	33.3	0.96
3302	15	42	19	0.132	3311	55	120	49.2	2.53
3202	17	40	17.5	0.1	5311	55	120	49.2	2.3
5203	17	40	17.5	0.091	3212	60	110	36.5	1.4
3303	17	47	22.2	0.192	5212	60	110	36.5	1.36
3204	20	47	20.6	0.17	3312	60	130	54	3.24
5204	20	47	20.6	0.12	5312	60	130	54	3.16
3304	20	52	22.2	0.23	3213	65	120	38.1	1.75
5304	20	52	22.2	0.23	5213	65	120	38.1	1.66
3205	25	52	20.6	0.19	3313	65	140	58.7	4.08
5205	25	52	20.6	0.19	5313	65	140	58.7	3.91
3305	25	62	25.4	0.369	3214	70	125	39.7	1.92
5305	25	62	25.4	0.34	5214	70	125	39.7	1.81
3206	30	62	23.8	0.32	3314	70	150	63.5	5.04
5206	30	62	23.8	0.29	5314	70	150	63.5	1.89
3306	30	72	30.2	0.585	3215	75	130	41.3	2.1
5206	30	72	30.2	0.51	3315	75	160	68.3	6.16
3207	35	72	27	0.48	5315	75	160	68.3	5.97
5207	35	72	27	0.43	3216	80	140	44.4	2.64
3307	35	80	34.9	0.816	3316	80	170	68.3	6.93
5307	35	80	34.9	0.79	3217	85	150	49.2	3.39
3208	40	80	30.2	0.65	3317	85	180	73	8.3
5208	40	80	30.2	0.57	3218	90	160	52.4	4.14
3308	40	90	36.5	1.07	3318	90	190	73	9.23
5308	40	90	36.5	1.05	3219	95	170	55.6	5
3209	45	85	30.2	0.71	3319	95	200	77.8	10.9
5209	45	85	30.2	0.62	3220	100	180	60.3	6.1
3309	45	100	39.7	1.42	3320	100	215	82.6	13.5
5309	45	100	39.7	1.42	3221	105	190	65.1	7.37
3210	50	90	30.2	0.76	3321	105	225	87.3	15.6
5210	50	90	30.2	0.76	3222	110	200	69.8	8.8
3310	50	110	44.4	1.95	3322	110	240	92.1	18.9

Note: We can also design and produce special kinds of bearings according to the requirements of customers.

If you need more information, please contact us.