

Single row angular contact ball bearings

Bearing Designation	Boundary Dimensions			Mass	Bearing Designation	Boundary Dimensions			Mass
	d	D	B	Approx		d	D	B	Approx
7900C	10	22	6	0.008	7204C	20	47	14	0.112
7000	10	26	8	0.021	7304	20	52	15	0.015
7000B	10	26	8	0.021	7304B	20	52	15	0.015
7000C	10	26	8	0.021	7304C	20	52	15	0.015
7200	10	30	9	0.031	7404	20	72	19	0.395
7200B	10	30	9	0.031	7404C	20	72	19	0.395
7200C	10	30	9	0.031	7905C	25	42	9	0.041
7300	10	35	11	0.054	7005	25	47	12	0.091
7901C	12	24	6	0.01	7005B	25	47	12	0.091
7001	12	28	8	0.024	7005C	25	47	12	0.091
7001B	12	28	8	0.024	7205	25	52	15	0.135
7001C	12	28	8	0.024	7205B	25	52	15	0.135
7201	12	32	10	0.038	7205C	25	52	15	0.135
7201B	12	32	10	0.038	7305	25	62	17	0.243
7201C	12	32	10	0.038	7305B	25	62	17	0.243
7301	12	37	12	0.065	7305C	25	62	17	0.243
7902C	15	28	7	0.015	7405	25	80	21	0.527
7002	15	32	9	0.035	7405B	25	80	21	0.527
7002B	15	32	9	0.035	7906C	30	47	9	0.046
7002C	15	32	9	0.035	ACH006C	30	55	13	0.122
7202	15	35	11	0.048	7006	30	55	13	0.133
7202B	15	35	11	0.048	7006B	30	55	13	0.133
7202C	15	35	11	0.048	7006C	30	55	13	0.133
7302	15	42	13	0.048	7206	30	62	16	0.208
7903C	17	30	7	0.016	7206B	30	62	16	0.208
7003	17	35	10	0.045	7206C	30	62	16	0.208
7003B	17	35	10	0.045	7306	30	72	19	0.362
7003C	17	35	10	0.045	7306B	30	72	19	0.362
7203	17	40	12	0.07	7306C	30	72	19	0.362
7203B	17	40	12	0.07	7406	30	90	23	0.686
7203C	17	40	12	0.07	7406B	30	90	23	0.686
7303	17	47	14	0.12	7907C	35	55	10	0.074
7303B	17	47	14	0.12	ACH007C	35	62	14	0.162
7303C	17	47	14	0.12	7007	35	62	14	0.17
7904C	20	37	9	0.035	7007B	35	62	14	0.17
7004	20	42	12	0.079	7007C	35	62	14	0.17
7004B	20	42	12	0.079	7207	35	72	17	0.295
7004C	20	42	12	0.079	7207B	35	72	17	0.295
7204	20	47	14	0.112	7207C	35	72	17	0.295
7204B	20	47	14	0.112	7307	35	80	21	0.475
7307B	35	80	21	0.475	ACH911C	55	80	13	0.195
7307C	35	80	21	0.475	ACH011C	55	90	18	0.413
7407	35	100	25	0.95	7011	55	90	18	0.42
7407B	35	100	25	0.95	7011B	55	90	18	0.42
7908C	40	62	12	0.107	7011C	55	90	18	0.42
ACH008C	40	68	15	0.203	7211	55	100	21	0.635
7008	40	68	15	0.21	7211B	55	100	21	0.635
7008B	40	68	15	0.21	7211C	55	100	21	0.635
7008C	40	68	15	0.21	7311	55	120	29	1.45
7208	40	80	18	0.382	7311B	55	120	29	1.45
7208B	40	80	18	0.382	7311C	55	120	29	1.45

Zhejiang Zhengda Bearing Co., Ltd

Zhejiang Zhengda Automobile Bearing Co., Ltd.

Phone: 086-577-62665675, 62665678 Fax: 086-577-62665679

Email: webmaster@zd-bearing.com zl@zl.zjbnet.com

Website: <http://www.bearing-in-china.com>

7208C	40	80	18	0.382	7411	55	140	33	2.36
7308	40	90	23	0.657	7411B	55	140	33	2.36
7308B	40	90	23	0.657	7912C	60	85	13	0.187
7308C	40	90	23	0.657	ACH912C	60	85	13	0.209
7408	40	110	27	1.23	ACH012C	60	95	18	0.442
7408B	40	110	27	1.23	7012	60	95	18	0.45
7909C	45	68	12	0.127	7012B	60	95	18	0.45
ACH009C	45	75	16	0.258	7012C	60	95	18	0.45
7009	45	75	16	0.26	7212	60	110	22	0.82
7009B	45	75	16	0.26	7212B	60	110	22	0.82
7009C	45	75	16	0.26	7212C	60	110	22	0.82
7209	45	85	19	0.43	7312	60	130	31	1.81
7209B	45	85	19	0.43	7312B	60	130	31	1.81
7209C	45	85	19	0.43	7312C	60	130	31	1.81
7309	45	100	25	0.875	7412	60	150	35	2.85
7309B	45	100	25	0.875	7412B	60	150	35	2.85
7309C	45	100	25	0.875	7913C	65	90	13	0.205
7409	45	120	29	1.55	ACH913C	65	90	13	0.223
7409B	45	120	29	1.55	ACH013C	65	100	18	0.471
7910C	50	72	12	0.128	7013	65	100	18	0.47
ACH910C	50	72	12	0.139	7013B	65	100	18	0.47
ACH010C	50	80	16	0.279	7013C	65	100	18	0.47
7010	50	80	16	0.29	7213	65	120	23	1.02
7010B	50	80	16	0.29	7213B	65	120	23	1.02
7010C	50	80	16	0.29	7213C	65	120	23	1.02
7210	50	90	20	0.485	7313	65	140	33	2.22
7210B	50	90	20	0.485	7313B	65	140	33	2.22
7210C	50	90	20	0.485	7313C	65	140	33	2.22
7310	50	110	27	1.14	7413	65	160	37	3.41
7310B	50	110	27	1.14	7413B	65	160	37	3.41
7310C	50	110	27	1.14	7914C	70	100	16	0.332
7410	50	130	31	1.92	ACH914C	70	100	16	0.369
7410B	50	130	31	1.92	ACH014C	70	110	20	0.642
7911C	55	80	13	0.178	7014	70	110	20	0.66
7014B	70	110	20	0.66	7217B	85	150	28	1.87
7014C	70	110	20	0.66	7217C	85	150	28	1.87
7214	70	125	24	1.12	7317	85	180	41	4.53
7214B	70	125	24	1.12	7317B	85	180	41	4.53
7214C	70	125	24	1.12	7317C	85	180	41	4.53
7314	70	150	35	2.7	7417	85	210	52	8.54
7314B	70	150	35	2.7	7417B	85	210	52	8.54
7314C	70	150	35	2.7	7918C	90	125	18	0.551
7414	70	180	42	4.99	ACH918C	90	125	18	0.615
7414B	70	180	42	4.99	ACH018C	90	140	24	1.23
7915	75	105	16	0.35	7018	90	140	24	1.26
ACH915C	75	105	16	0.391	7018B	90	140	24	1.26
ACH015C	75	115	20	0.677	7018C	90	140	24	1.26
7015	75	115	20	0.69	7218	90	160	30	2.3
7015B	75	115	20	0.69	7218B	90	160	30	2.3
7015C	75	115	20	0.69	7218C	90	160	30	2.3
7215	75	130	25	1.23	7318	90	190	43	5.3
7215B	75	130	25	1.23	7318B	90	190	43	5.3
7215C	75	130	25	1.23	7318C	90	190	43	5.3
7315	75	160	37	3.15	7418	90	225	54	11.4
7315B	75	160	37	3.15	7418B	90	225	54	11.4

Zhejiang Zhengda Bearing Co., Ltd
Zhejiang Zhengda Automobile Bearing Co., Ltd.
Phone: 086-577-62665675, 62665678 Fax: 086-577-62665679
Email: webmaster@zd-bearing.com zl@zl.zjbnet.com
Website: <http://www.bearing-in-china.com>

7315C	75	160	37	3.15	7919C	95	130	18	0.574
7415	75	190	45	5.9	ACH919C	95	130	18	0.644
7415B	75	190	45	5.9	ACH019C	95	145	24	1.28
7916C	80	110	16	0.368	7019	95	145	24	1.32
ACH916C	80	110	16	0.412	7019B	95	145	24	1.32
ACH016C	80	125	22	0.915	7019C	95	145	24	1.32
7016	80	125	22	0.93	7219	95	170	32	2.78
7016B	80	125	22	0.93	7219B	95	170	32	2.78
7016C	80	125	22	0.93	7219C	95	170	32	2.78
7216	80	140	26	1.5	7319	95	200	45	6.12
7216B	80	140	26	1.5	7319B	95	200	45	6.12
7216C	80	140	26	1.5	7319C	95	200	45	6.12
7316	80	170	39	3.85	7920C	100	140	20	0.773
7316B	80	170	39	3.85	ACH920C	100	140	20	0.869
7316C	80	170	39	3.85	ACH020C	100	150	24	1.34
7416	80	200	48	6	7020	100	150	24	1.37
7416B	80	200	48	6	7020B	100	150	24	1.37
7917C	85	120	18	0.523	7020C	100	150	24	1.37
ACH917C	85	120	18	0.586	7220	100	180	34	3.32
ACH017C	85	130	22	0.959	7220B	100	180	34	3.32
7017	85	130	22	0.97	7220C	100	180	34	3.32
7017B	85	130	22	0.97	7320	100	215	47	7.53
7017C	85	130	22	0.97	7320B	100	215	47	7.53
7217	85	150	28	1.87	7320C	100	215	47	7.53
7921C	105	145	20	0.81	7222	110	200	38	4.65
ACH921C3	105	145	20	0.907	7222B	110	200	38	4.65
ACH021C	105	160	26	1.7	7222C	110	200	38	4.65
7021	105	160	26	1.73	7322	110	240	50	10.1
7021B	105	160	26	1.73	7322B	110	240	50	10.1
7021C	105	160	26	1.73	7322C	110	240	50	10.1
7221	105	190	36	3.95	7924C	120	165	22	1.15
7221B	105	190	36	3.95	ACH924C	120	165	22	1.29
7221C	105	190	36	3.95	ACH024C	120	180	28	2.29
7321	105	225	49	8.62	7024	120	180	28	2.27
7321B	105	225	49	8.62	7024B	120	180	28	2.27
7321C	105	225	49	8.62	7024C	120	180	28	2.27
7922C	110	150	20	0.84	7224	120	215	40	5.49
ACH922C	110	150	20	0.942	7224B	120	215	40	5.49
ACH022C	110	170	28	2.13	7224C	120	215	40	5.49
7022	110	170	28	2.14	7324	120	260	55	12.6
7022B	110	170	28	2.14	7324B	120	260	55	12.6
7022C	110	170	28	2.14	7324C	120	260	55	12.6

Note: We can also design and produce special kinds of bearings according to the requirements of customers.

If you need more information, please contact us.